

Attorney's Docket No.: 06618/736001

Amendment to the Claims:

This listing of claims replaces all prior versions, and listings, of claims in the application:

1. (Previously presented) A device, comprising:

a first fiber having a first untapered fiber section which is a single-mode fiber for light at a first wavelength and a first tapered fiber section which has one end conforming to and connected to said first untapered fiber section and has a fiber diameter gradually reducing from said one end to another opposing end; and

a second fiber having a second untapered fiber section and a second tapered fiber section which has one end being spliced to said another opposing end of said first tapered fiber section and another end conforming to and connected to said second untapered fiber section, wherein a fiber diameter of said second tapered fiber section gradually increases from said one end to said another end, and

wherein said second untapered fiber section is a single-mode fiber for light at a second wavelength and has a core diameter greater than a diameter of a fiber core of said first untapered fiber section.

2. (Original) The device as in claim 1, wherein each fiber has a structural variation from a respective untapered fiber section to a respective tapered fiber section that satisfies an optical adiabatic transformation condition to transform optical energy in a single mode in either of said first and said second untapered fiber sections in said first and said second wavelengths, respectively, into optical energy in a mode in said first and said second tapered fiber sections.

Attorney's Docket No.: 06618/736001

3. (Original) The device as in claim 1, further comprising an optical element located in an evanescent field of guided optical energy in one of said first and said second tapered fiber sections to evanescently exchange optical energy at said first wavelength with said first fiber and exchange optical energy at said second wavelength with said second fiber.

4. (Original) The device as in claim 3, wherein said optical element includes a micro cavity that supports at least one whispering gallery mode at said first wavelength and one whispering gallery at said second wavelength.

5. (Original) The device as in claim 4, wherein said micro cavity is in direct contact with a respective tapered fiber section of one of said first and said second fibers.

6. (Original) The device as in claim 4, wherein said micro cavity is spaced from a respective tapered fiber section of one of said first and second fibers.

7. (Original) The device as in claim 4, wherein said micro cavity is a sphere.

8. (Original) The device as in claim 4, wherein said micro cavity is not a sphere.

9. (Original) The device as in claim 3, wherein said optical element is located to evanescently receive light at said first wavelength received from said first untapered fiber section and to evanescently couple light at said second wavelength through one of said first and said second tapered fiber sections into said second untapered fiber section.

Attorney's Docket No.: 06618/736001

10. (Original) The device as in claim 9, wherein said optical element includes an optical cavity.

11. (Original) The device as in claim 10, wherein said optical cavity is a ring cavity.

12. (Original) The device as in claim 10, wherein said optical cavity is a Fabry-Perot cavity.

13. (Currently Amended) A device, comprising:

an optical fiber coupler having a tapered fiber section formed of a fiber cladding material to form an optical waveguide based on interfacing between said fiber cladding material and air, a first single-mode fiber for light at a first wavelength connected to a first side of said tapered fiber section, and a second single-mode fiber for light at a second wavelength connected to a second side of said tapered fiber section,

wherein said tapered fiber section has a structure to support at least one waveguide mode at said first wavelength and one waveguide mode at said second wavelength, and said first and said second wavelengths are different.

14. (Original) The device as in claim 13, wherein each of said first and said second single-mode fibers is connected to said tapered fiber section under an optical adiabatic transformation condition to allow optical energy in a single mode in either of said first and said second single-mode fibers to transform into a waveguide mode in said tapered fiber section.

Attorney's Docket No.: 06618/736001

15. (Original) The device as in claim 13, further comprising a micro cavity that supports at least one whispering gallery mode at said first wavelength and one whispering gallery at said second wavelength and absorbs light at said first wavelength to produce light at said second wavelength, said micro cavity located relative to said tapered fiber section to evanescently receive light at said first wavelength from said tapered fiber section and to evanescently couple light at said second wavelength into said tapered fiber section.

16. (Original) The device as in claim 15, wherein said micro cavity is in direct contact with said tapered fiber portion.

17. (Original) The device as in claim 15, wherein said micro cavity is spaced from said tapered fiber portion.

18. (Original) The device as in claim 15, wherein said micro cavity is a dielectric material doped with rare-earth ions.

19. (Original) The device as in claim 15, wherein said micro cavity is a sphere.

20. (Original) The device as in claim 15, wherein said micro cavity is not a sphere.

21-23. (Canceled)

24. (Currently Amended) A device, comprising:
a tapered waveguide section to guide optical energy in at least one mode at a first wavelength and one mode at a second

Attorney's Docket No.: 06618/736001

wavelength and to expose an evanescent field of said guided optical energy outside said tapered waveguide section, wherein said first and said second wavelengths are different;

a first waveguide section supporting a first single mode at said first wavelength and connected to a first side of said tapered waveguide section to allow for conversion of optical energy between said one mode at said first wavelength in said tapered waveguide section and said first single mode; and

a second waveguide section supporting a second single mode at said second wavelength and connected to a second side of said tapered waveguide section to allow for conversion of optical energy between said one mode at said second wavelength in said tapered waveguide section and said second single mode.

25. (Original) The device as in claim 24, wherein one of said waveguide sections is formed of a fiber.

26. (Original) The device as in claim 24, wherein one of said waveguide sections is formed of a planar waveguide on a substrate.

27. (Original) The device as in claim 24, further comprising an optical element located to evanescently couple light at said first wavelength from said tapered waveguide section and to evanescently couple light at said second wavelength into said tapered fiber section.

28. (Original) The device as in claim 27, wherein said optical element includes an optical cavity.

29. (Original) The device as in claim 28, wherein said optical cavity is a whispering-gallery-mode cavity.

Attorney's Docket No.: 06618/736001

30. (Previously presented) A device, comprising:

an optical resonator including a laser gain medium that absorbs light at a first wavelength to produce an optical gain at a second wavelength longer than said first wavelength and to produce laser light at said second wavelength; and

an optical coupler to optically couple light at said first wavelength into said optical resonator and to couple laser light at said second wavelength out of said optical resonator, wherein said optical coupler includes:

a tapered waveguide section, located adjacent to said optical resonator, to guide optical energy at said first wavelength and said second wavelength and to expose an evanescent field of said guided optical energy outside said tapered waveguide section to allow for evanescent coupling with said optical resonator at said first and said second wavelengths,

a first waveguide section supporting a single mode at said first wavelength and connected to a first side of said tapered waveguide section to receive and direct light at said first wavelength to said tapered waveguide section, and

a second waveguide section supporting a second single mode at said second wavelength and connected to a second side of said tapered waveguide section to receive laser light at said second wavelength from said tapered waveguide section to produce a laser output.

31. (Previously presented) The device as in claim 30, wherein said first and said second waveguide sections are a first single-mode fiber at said first wavelength and a second single-mode fiber at said second wavelength.

Attorney's Docket No.: 06618/736001

32. (Previously presented) The device as in claim 30,
wherein said optical resonator is a whispering gallery mode
resonator.